

KDTW

Detroit Metropolitan Wayne County Detroit, MI

15.00 mi S of city N42 12.7467' W83 21.2033' Mag Var: 07W

Nav aids:

Type:	ID:	Freq:	Radial:	Dist:
VOR/DME	DXO --- ---	113.40	100	1 nm
VOT	DTW --- - ---	109.80	000	1 nm
VOT	YIP ---- .. ----	112.0	000	8 nm

Traffic Patterns:

Airport Manager:	Aircraft	Altitude (MSL)
	Light Aircraft	1645

Runways:

03L/21R: 8501X200; asphalt, concrete, grooved, in good condition; Pole, 569 ft Left of center, 19 ft high, 698 ft from end, 26:1 clearance slope; Pole, 179 ft Right of center, 42 ft high, 2,302 ft from end, 50:1 clearance slope;

03R/21L: 10001X150; concrete, concrete, grooved, in excellent condition; Berm, 529 ft Left of center, 19 ft high, 359 ft from end, 8:1 clearance slope;

04L/22R: 10000X150; concrete, concrete, grooved, in excellent condition; Tree, 157 ft Right of center, 48 ft high, 2,563 ft from end, 49:1 clearance slope; Road, 545 ft Right of center, 14 ft high, 550 ft from end, 25:1 clearance slope;

04R/22L: 12003X200; concrete, concrete, grooved, in excellent condition; Tree, 159 ft Right of center, 75 ft high, 3,602 ft from end, 45:1 clearance slope; Railroad, 597 ft Right of center, 27 ft high, 1,081 ft from end, 33:1 clearance slope;

04X/22X: 0X0; concrete, no surface treatment, condition not reported;

09L/27R: 8708X150; concrete, grooved, in excellent condition; Antenna, 461 ft Right of center, 107 ft high, 4,461 ft from end, 40:1 clearance slope; Berm, 373 ft Right of center, 7 ft high, 333 ft from end, 19:1 clearance slope;

09R/27L: 8500X150; concrete, grooved, in excellent condition; Antenna, 461 ft Right of center, 107 ft high, 4,461 ft from end, 40:1 clearance slope;


Elevation 645 ft (196.6 m)

Noise Abatement:

In effect; informal flight ops restriction; ctd 942-3555
Published Noise rule

Communication Frequencies are printed on the following page.

Tower: Tower Hrs: 24
Primary Depart. Control Hrs: 24
Primary Approach Control Hrs: 24



Communication Freqs:

App 125.15 (;RWY 03R, 21L, 27R)

App 124.05 (;RWY 04L, 04R, 22L, 22R, 27L)

WX 734-955-5015

BARII DP 132.025 (;RWY 21L/R, 3L/R 27L/R)

BARII DP 125.525 (;RWY 22L/R, 4L/4R)

BONZZ STAR 126.225

CCOBB DP 132.025 (;RWY 27L/R)

CCOBB DP 125.525 (;RWY 3L/R, 4L/R, 21L/R, 22L/R)

Clnc-Del PRE TAXI CLNC 120.65

CLASS B 134.3 (;(SE)

CLASS B 118.95 (;(SW)

CLASS B 132.35 (;(NW/NE)

CLVIN DP 132.025 (;RWY 21L/R, 3L/R, 27L/R)

CLVIN DP 125.525 (;RWY 22L/R, 4L/4R)

CRAKN STAR 126.225

CUUGR STAR 126.225

D-ATIS 133.675 (;ARR)

D-ATIS 118.125 (;(DEP)

DEP/P 132.025 (;(TURBOJETS-EAST) DEP/P 125.525

(;(TURBOJETS-WEST)

DEP/P 134.3 (;(PROPS/TURBOPROPS-EAST)

DEP/P 118.95 (;(PROPS/TURBOPROPS-WEST)

FERRL STAR 126.225

GEMNI STAR 126.225

Gnd 119.45 (;(NORTHEAST)

Gnd 121.8 (;(NORTHWEST)

Gnd 119.25 (;(SOUTHEAST)

Gnd 132.725 (;(SOUTHWEST)

GRAYT STAR 124.975

HANBLSTAR 124.975

HAYLL STAR 124.975

HHOWE DP 132.025 (;RWY 21L/R, 22L/R, 3L/R, 4L/R)

HHOWE DP 125.525 (;RWY 27L/R)

HTROD STAR 126.225

KAYLN DP 125.525

KKISS STAR 124.975

KLYNK STAR 126.225

LAYKS STAR 124.975

Tower 128.75 (;ARRIVAL RWY 03L/21R, 27L)

Tower 118.4 (;ARRIVAL RWY 03R/21L, 27R)

Tower 135.0 (;ARRIVAL RWY 04L/22R)

Tower 128.125 (;ARRIVAL RWY 04R/22L)

Tower 118.4 (;(DEP, ARPT DIAG RWY 03L/21R, 03R/21L,)

Tower 135.0 (;(DEP, ARPT DIAG RWY 04L/22R, 04R/22L)

Tower 128.75 (;(DEP, ARPT DIAG RWY 27L)

LECTR STAR 124.975

LIDDS DP 132.025

METRO DP 134.3 (;(EASTBOUND)

METRO DP 118.95 (;(WESTBOUND)

MIGGY DP 125.525

MIZAR STAR 124.975

PAVYL DP 132.025

POLAR STAR 124.975

PRM 127.05 (;RWY 04L/22R)

PRM 135.775 (;RWY 04R/22L)

RKCTY STAR 124.975

SNDRS DP 132.025 (;RWY 21L/R, 3L/R, 27L/R)

SNDRS DP 125.525 (;RWY 22L/R, 4L/4R)

SPICA STAR 126.225

TPGUN STAR 126.225

TRMML DP 132.025 (;RWY 21L/R)

TRMML DP 125.525 (;RWY 22L/R, 3L/R, 4L/R, 27L/R)

UNICOM 122.95

VCTRZ STAR 124.975

WEEDA STAR 126.225

WNGNT STAR 126.225

ZETTR DP 132.025 (;RWY 21L/R)

ZETTR DP 125.525 (;RWY 22L/R, 3L/R, 4L/R, 27L/R)



AIRPORT DIAGRAM

DETROIT METROPOLITAN WAYNE COUNTY (DTW)
DETROIT, MICHIGAN
AL-119 (FAA)

D-ATIS ARR 133.675
DEP 118.125
METRO TOWER
118.4 (RWY 03L-21R, 03R-21L, 27R)
128.75 (RWY 27L)
135.0 (RWY 04L-22R, 04R-22L)
317.725
CLNC DEL
120.65
CPDLC

RWY 03L-21R
PCN 77 R/A/W/T
S-100, D-185, 2D-350
RWY 03R-21L
PCN 91 R/B/W/T
S-100, D-200, 2D-350, 2D/2D2-750
RWY 04L-22R
PCN 126 R/B/W/T
S-100, D-200, 2D-350, 2D/2D2-750
RWY 04R-22L
PCN 126 R/B/W/T
S-100, D-185, 2D-350
RWY 09L-27R
PCN 73 R/A/W/T
S-100, D-185, 2D-350
RWY 09R-27L
PCN 78 R/A/W/T
S-100, D-185, 2D-350

NORTHWEST
GND CON
121.8

U.S. CUSTOMS AND
GENERAL AVIATION

NORTHEAST
GND CON
119.45

JANUARY 2015
ANNUAL RATE OF CHANGE
0.0° W

Runway Status
lights in operation.

EC-1, 20 JUN 2019 to 18 JUL 2019

EC-1, 20 JUN 2019 to 18 JUL 2019

ASDE-X in use. Operate transponders
with altitude reporting mode and ADSB
(if equipped) enabled on all airport surfaces.

CAUTION: BE ALERT TO RUNWAY CROSSING CLEARANCES.
READBCK OF ALL RUNWAY HOLDING INSTRUCTIONS IS REQUIRED.

AIRPORT DIAGRAM

DETROIT METROPOLITAN WAYNE COUNTY (DTW)
DETROIT, MICHIGAN
19003

